



PAINT & VARNISH REMOVER

PRODUCT DESCRIPTION

Type: A jelly-like, corrosive paste based on strong solvent, wax and a salt

Uses: For stripping oil based (and water based) paints and varnishes from previously painted substrates

Substrates: Metals, wood, brick, stone, plaster, concrete and masonry painted in alkyd based gloss/ eggshell enamels, undercoats, primers etc in addition to Nitrocellulose and a number of industrial finishes. Crown Paint and Varnish Remover can also be used on water based paints. Its efficacy will be greatly reduced when used to remove old coatings, Stoving and 2-pack paints in sound condition, where more than one coat may be required.

Advantages: Non-flammable. Water based. Cost effective, easy to apply and use. Easy clean up with running water

Conditions during application; The temperature of the substrate should be minimum 10°C and at least 3°C above the dew point of the air, measured in the vicinity of the substrate. Good ventilation is usually required in confined areas to ensure proper drying. The moisture content in the substrate should not exceed 3% (by weight). The coating should not be exposed to oil, chemicals or mechanical stress until fully cured.

PRODUCT DATA:

Colour Range: Clear/ Off white

Pack Sizes: ½L, 1 Litre and 5Litres

Finish: Matt

Thinner & equipment cleaner: Water

Dilution Ratio: Supplied ready for use. Do not thin. Stir well before use.

Application: It is advisable to apply a test patch to test substrate sensitivity. Apply the paint remover generously with an ordinary brush or plastic spatula, avoiding unnecessary splashing of the skin or other surfaces. Leave for at least 15 minutes then remove the paint with a scraper or shave hook. When removing several coats of paint, additional applications may be necessary. The paint remover will continue to be active for a considerable time after application. After all paint has been stripped, the surface should be rinsed with clean water and then allowed to dry thoroughly before overcoating.

Drying Times: Leave on the surface for about 15 minutes to 36 hours (depending on strength of coating and number of coats) then rinse with clean water to remove residues. DO not allow the paint remover to dry on the substrate before rinsing.

APPLICATION DATA:

The product can be applied by: Brush or Roller (on flat surfaces) or Spatula

Spreading Capacity per coat: Depends on film thickness applied, type of texture, surface porosity, imperfections, temperature & wastage during painting

DISCLAIMER: The technical information provided on this data sheet is for your guidance and usage. Such information is based on Crown Paints experience and research and is believed to be reliable. As we have no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes. The information may be modified by us from time to time, and without notice, based on our experience and continuous product development



3 -4 m²/l

DIRECTIONS FOR USE

Surface preparation & Paint System:

Surface	Preparation	1 st coat	2 nd coat
Previously painted metal, wood or masonry surface	Ensure substrate is dry and free of dust and dirt	1 liberal coat Crown Paint and Varnish Remover	Only if 1 st coat has not been effective. 1 liberal coat Crown Paint and Varnish Remover

Availability: From Crown Depots in Nairobi, Kisumu, Mombasa, Meru, Kampala, Arusha, Mwanza, Dar es Salaam, Kigali and through Crown Stockists.

Precautions:

1. Open tins slowly and carefully, with the lid facing away due to pressure build up which may occur in storage.
2. Material contains corrosive ingredients
3. Wear adequate protective clothing during use and avoid skin contact
4. Ensure adequate ventilation during use
5. Discard any leftover materials in accordance with local regulation.

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

DISCLAIMER: The technical information provided on this data sheet is for your guidance and usage. Such information is based on Crown Paints experience and research and is believed to be reliable. As we have no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes. The information may be modified by us from time to time, and without notice, based on our experience and continuous product development